AIRMASTER DELUXE FAIRING 1336

PARTS INCLUDED

1	Air Master™ Deluxe Fairing with Audio System-Road King
1	Fairing Wiring Kit
1	Dragon Wing Spacer Kit
1	Sony DSX-S100 Manual and Accessories
2	Cigarette Lighter/Power Points
1	GPS Rubber Block Mount
1	Stereo "Weather" Cover
1	Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

ATTENTION! **This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.**

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

TOOLS SUGGESTED

Set of Hex Wrenches, Socket Set with Ratchet and Combination Wrenches, Test Light

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let cool.

NOTE: **The installation of the AirMaster Fairing requires the appropriate mounting kit for your application. (Sold Separately)**

WARNING! IF INSTALLING THIS PRODUCT FOR ANOTHER PARTY, PLEASE MAKE SURE THEY RECEIVE THIS COPY OF THE INSTALLATION INSTRUCTIONS SO THEY ARE AWARE OF THESE IMPORTANT WARNINGS.

WARNING! YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

-cont.-

CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breech of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Küryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Küryakyn makes no warranty of any kind in regard to other manufacturer¹s products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

For purchasing Küryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Küryakyn, P.O. Box 339, Somerset, WI 54025. Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.

kuryakyn.com

ATTENTION! **A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all of the steps in the procedure; consult a trained technician.**

WARNING! ANY MODIFICATION TO THE MOTORCYCLE, LIKE ADDING A FAIRING OR WINDSHIELD, WILL HAVE AN EFFECT ON THE MOTORCYCLE'S SLOW AND HIGH SPEED HANDLING. FAMILIARIZE YOURSELF WITH THE ADDED WEIGHT AND DIFFERENT LINE OF SIGHT BEFORE RIDING THE MOTORCYCLE FOR THE FIRST TIME. THE ADDED WIND PROTECTION FROM THE FAIRING MAY AFFECT YOUR JUDGMENT OF SPEED. THE EFFECT OF CROSSWINDS OR OF THE WIND CREATED FROM PASSING LARGE VEHICLES MAY AFFECT THE HANDLING OF THE MOTORCYCLE. BE AWARE OF THESE DIFFERENCES AND OTHERS THAT MAY ARISE. FAILURE TO COMPENSATE FOR WITH THESE DIFFERENCES MAY CAUSE LOSS OF CONTROL RESULTING IN SERIOUS INJURY OR DEATH.

WARNING! SET ALL RADIO CONTROLS WHILE STOPPED. DO NOT ATTEMPT TO ADJUST YOUR RADIO CONTROLS WHILE OPERATING THE MOTORCYCLE.

WARNING! ENSURE THAT THE FAIRING AND MOUNTING HARDWARE DO NOT INTERFERE WITH ANY CABLES, WIRING OR WITH THE FUEL TANK ON THE MOTORCYCLE WHEN THE FORK IS TURNED LOCK TO LOCK.

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

CONNECTING POWER WIRES

STEP 2 Remove the seat to gain access to the battery.

STEP 3 Remove the instrument panel (Dash Panel). Plug the harness from the fairing to the wiring harness, route the wiring harness back to the battery.

STEP 4 Take the wiring harness ends and connect positive and negative fork terminals to the positive and negative mounts on the battery.

NOTE: **The positive wire has an in-line fuse.**

STEP 5 Connect the wire labeled "switch power" to keyed 12V power. This allows the stereo to power up only when the key is in the "On" position.

NOTE: **Connecting this wire to constant power will result in battery drain.**

ATTENTION! **Secure all wiring away from any moving parts, pinch points or extreme heat. Küryakyn WILL NOT issue a warranty on any electrical component that fails due to pinched, crimped, broken, abraded, melted or frayed wires.**

STEP 5 Tuck the wiring harness away and re-mount the instrument panel

STEP 6 Secure any excess wiring out of the way and replace the seat.

WARNING! AFTER INSTALLING THE SEAT, PULL UP ON IT TO ENSURE IT IS LOCKED INTO PLACE. A LOOSE SEAT CAN SHIFT AND CAUSE LOSS OF CONTROL RESULTING IN SERIOUS INJURY OR DEATH.

-cont.-

FAIRING FEATURES

- The Airmaster fairing has many features and options, making it very user friendly.
- Inside the box you will find a non-slide rubber mat, a cigarette lighter/power point, keys, stereo instructions and the stereo "weather" cover. Also, a spacer kit that will be included that will be needed if you wish to install the Küryakyn Dragon Wings sold separately. (Küryakyn P/N 1117 or 1108)

NOTE: The Dragon Wing spacer kit is needed when installing the Küryakyn Dragon wings; they allow smooth operation of the Dragon Wings. Place the spacers behind the center and top Dragon Wing mounting hole locations.

- Refer to included Sony manual for information or receiver operation and use.
- The cigarette lighter/power point is for use for any type of charging you may need (i.e. cell phone ect…) You may also use it for the lighter function. The fairing also has an alternative cigarette lighter/power point. It is located to the lower left hand side just below the handlebars.
- The GPS rubber block mount is an option that we provided to make the installation of a GPS easier for the customers. On the inside of the fairing storage compartment door, you will find four preformed holes that line up with the rubber block mount. Using a drill, you can drill the four holes on the inside of the fairing storage compartment door. Once the holes are drilled, you will be able to take the rubber block mount and place it between the GPS and the fairing storage compartment door to help absorb some of the vibration from the bike as well as allowing the GPS to mount flat on the door.
- The Stereo "weather" cover is needed when you wish to wash the bike or for use when you store the bike. Place the tabs on the right side of the cover into the two slots on the right side of the stereo opening. Gently snap the left side into place and make sure that it is securely in place.

ATTENTION! When washing your bike, try to avoid excessive water usage around the stereo and speaker areas. Too much water contact could potentially damage the components in this fairing.

CARE and MAINTENANCE

CAUTION! Clean only with warm water and a mild, non-abrasive soap. Some cleaning products contain harsh chemicals that can severely damage product and void warranty.

CAUTION! Do not clean Lexan® polycarbonate in hot sun or high temperature. Powdered, abrasive or alkaline cleanser will damage the windshield and f airing. Never scrape the windshield or fairing with a razor blade or other sharp instrument.

CAUTION! Do not use benzene, paint thinner, gasoline or any other type of harsh cleaner on the windshield. Do not use ammonia based solvents or petroleum distillates. Doing so will damage the windshield and fairing surface.

CAUTION! Do not use harsh chemicals including rain sheeting products on motorcycle windshields or fairing. They can cause a dulling or hazing. To obtain a proper high-end polish, please use a quality protector and polish such as Plexus® or Novus® brand cleaners on the windshield and an automotive quality wax or polish on painted fairing.

NOTE: Sunlight reflections off the inside curvature of the windshield can, at certain times of the day, cause extreme heat build-up on motorcycle instruments. Exercise care in parking. Park facing the sun, place an opaque object over the instruments, or adjust the windshield to avoid reflections.